

642-611

Cisco

Implementing Cisco MPLS Exam (MPLS)

OfficialCerts.com is a reputable IT certification examination guide, study guides and audio exam provider. We ensure that you pass your 642-611 exam in first attempt and also get high scores to acquire Cisco certification.

If you use OfficialCerts 642-611 Certification questions and answers, you will experience actual 642-611 exam questions/answers. We know exactly what is needed and have all the exam preparation material required to pass the exam. Our Cisco exam prep covers over 95% of the questions and answers that may be appeared in your 642-611 exam. Every point from pass4sure 642-611 PDF, 642-611 review will help you take Cisco 642-611 exam much easier and become Cisco certified.

Here's what you can expect from the OfficialCerts Cisco 642-611 course:

- * Up-to-Date Cisco 642-611 questions as experienced in the real exam.*
- * 100% correct Cisco 642-611 answers you simply can't find in other 642-611 courses.*
- * All of our tests are easy to download. Your file will be saved as a 642-611 PDF.*
- * Cisco 642-611 brain dump free content featuring the real 642-611 test questions.*

Cisco 642-611 certification exam is of core importance both in your Professional life and Cisco certification path. With Cisco certification you can get a good job easily in the market and get on your path for success. Professionals who passed Cisco 642-611 exam training are an absolute favorite in the industry. You will pass Cisco 642-611 certification test and career opportunities will be open for you.

<http://news.ift.org/?newsid=exams.asp?examcode=642-611>



QUESTION 1:

Which statement is true about the hardware requirements of MPLS?

- A. Because you do not need to run a routing protocol on P-routers, they require less memory than routers supporting classic IP routing.
- B. Because of the additional processing and memory requirements needed to build the LFIB, MPLS is only available on high end routers.
- C. MPLS is available on low end routers, built their use is limited because of the additional processing and memory requirements needed to build the LFIB.
- D. Because P-routers do not need to carry routes outside the MPLD domain, they require less memory than routers that support the same application using classic IP routing.

Answer: C

QUESTION 2:

If aggregation (summarization) were to be used on a network with ATM LSRs. What would result?

- A. LSPs would be broken in two.
- B. There would be extra LFIB entries.
- C. The size of the LFIB table would increase.
- D. There would be extra LIB entries

Answer: A

QUESTION 3:

What is true of MPLS TE?

- A. Only the ingress LSR must see the entire topology of the network.
- B. Every LSR needs additional information about links in the network, available resources, and constraints.
- C. Every core router must be able to create an LSP tunnel on demand.
- D. Both RSVP and CR-LDP are used in conjunction to establish traffic engineering (TE) tunnels and to propagate the labels.

Answer: B

QUESTION 4:

What is a major drawback of using traditional IP routing over an ATM network when connecting multiple sites?

642-611

- A. Each ATM switch in the path has to perform Layer 3 routing lookup.
- B. ATM virtual circuits have to be established between the different sites.
- C. There is high ATM management overhead between the ATM switch and the router at each site.
- D. Each ATM switch has to be manually configured to participate in Layer 3 routing.
- E. There is high PNNI overhead.-

Answer: B

Explanation:

Drawbacks of Traditional IP Forwarding IP over ATM

- 1) Layer 2 devices have no knowledge of Layer 3 routing information - virtual circuits must be manually established.
- 2) Layer 2 topology may be different from Layer 3 topology, resulting in suboptimal paths and link use.
- 3) Even if the two topologies overlap, the hub-and-spoke topology is usually used because of easier management.

QUESTION 5:

What is true of MPLS TE?

- A. Only the ingress LSR must see the entire topology of the network.
- B. Every LSR needs additional information about links in the network, available resources, and constraints.
- C. Every core router must be able to create an LSP tunnel on demand.
- D. Both RSVP and CR-LDP are used in conjunction to establish traffic engineering (TE) tunnels and to propagate the labels.

Answer: B

QUESTION 6:

In order for MPLS to be implemented on ATM switches, what requirements must the ATM switch meet? Select two.

- A. become Layer 3 aware by running a routing protocol
- B. use MPLS LDP or TDP to distribute and receive MPLS label information
- C. use BGP to exchange MPLS VPN labels in the data plane
- D. use RSVP to exchange MPLS traffic-engineering labels in the data plane
- E. establish a full mesh of Layer 2 ATM virtual circuits between all the ATM switches in the MPLS domain
- F. use cell-mode MPLS and insert MPLS label in the ATM AAL5 header

Answer: A, B

QUESTION 7:

When running basic MPLS in conjunction with VPNs, how many labels does each packet contain?

- A. Each packet contains one label that identifies the VPN.
- B. Each packet contains at least two labels. One label identifies the path to the egress router and one that identifies the VPN.
- C. Each packet contains at least three labels. One label identifies the ingress router, one identifies the egress router and one identifies the path that will be taken.
- D. Each packet contains at least three labels. One label identifies the ingress router, one label identifies the path to the egress router, and one identifies the VPN.

Answer: B

QUESTION 8:

On ingress, a label is imposed to a packet. Which process is responsible for this function?

- A. LDP process.
- B. Control plane process
- C. Penultimate hop process.
- D. Forwarding plane process.

Answer: B

QUESTION 9:

How could you check for potential MTU size issues on the path taken by a PE-to-PE LSP?

- A. Because MPLS packets are label switched, MTU problems can only be detected by the user applications.
- B. Use the ping vrf command with packet size set to the largest MTU along the path and DF bit set from the local PE-router to ping the remote PE-router.
- C. Use the ping vrf command with packet size set to the smallest MTU along the path and DF bit set from the local PE-router to ping the remote PE-router.
- D. Because MPLS packets are label switched, packets are automatically fragmented and reassembled by the PE-routers.
Therefore, there are no potential MTU issues.

Answer: A D

QUESTION 10:

642-611

Which one of the following is true regarding MPLS independent control label allocations?

- A. The LSR can always assign a label for a destination prefix, even if it has no downstream label.
- B. The LSR can assign a label for a destination prefix only if it has already receives a label from the next-hop LSR, otherwise, it must request a label from the next-hop LSR.
- C. The LSR will assign a label to a destination prefix only when asked for a label by an upstream LSR.
- D. The label for a destination prefix is allocated and advertised to all LDP peers, regardless of whether the LDP peers are upstream or downstream LSRs for the destination prefix.
- E. The LSR stores the receives label in its LIB, even when the label is not received from the next-hop LSR.
- F. The LSR stores only the labels received from the next-hop LSR, all other labels are ignored.

Answer: A

QUESTION 11:

Which two statements are true about the label stack used for MPLS VPNs? (Choose two)

- A. The first label in the label stack is the VPN label assigned by the egress PE router.
- B. The first label in the label stack is the LDP label used to reach the egress PE router.
- C. The first label in the label stack is the VPN label used to reach the egress PE router.
- D. The second label in the label stack is the VPN label assigned by the egress PE router.
- E. The second label in the label stack is the LDP label used to each the egress PE router.
- F. The second label in the label stack is the VPN label assigned by the ingress PE router and tells the ingress PE router how to forward the incoming VPN packet.

Answer: B, D

QUESTION 12:

What is true about how MPLS implementations support different applications?

- A. The applications only differ in the control plane.
- B. The forwarding plane is customized for each application.
- C. MPLS VPNs require RSVP.
- D. In general a FEC is assigned to a label.

Answer: A

QUESTION 13:

OfficialCerts.com Certification Exam Full Version Features;

- Verified answers researched by industry experts.
- Exams **updated** on regular basis.
- Questions, Answers are downloadable in **PDF** format.
- **No authorization** code required to open exam.
- **Portable** anywhere.
- 100% success **Guarantee**.
- **Fast**, helpful support 24x7.

View list of All exams we offer;
<http://www.officialcerts.com/allexams.asp>

To contact our Support;
<http://www.officialcerts.com/support.asp>

View FAQs
<http://www.officialcerts.com/faq.asp>

Download All Exams Samples
<http://www.officialcerts.com/samples.asp>

To purchase Full Version and updated exam;
<http://www.officialcerts.com/allexams.asp>



Shop now using **PayPal**



3COM	CompTIA	Filemaker	IBM	LPI	OMG	Sun
ADOBE	ComputerAssociates	Fortinet	IISFA	McAfee	Oracle	Sybase
APC	CWNP	Foundry	Intel	McData	PMI	Symantec
Apple	DELL	Fujitsu	ISACA	Microsoft	Polycom	TeraData
BEA	ECCouncil	GuidanceSoftware	ISC2	Mile2	RedHat	TIA
BICSI	EMC	HDI	ISEB	NetworkAppliance	Sair	Tibco
CheckPoint	Enterasys	Hitachi	ISM	Network-General	SASInstitute	TruSecure
Cisco	ExamExpress	HP	Juniper	Nokia	SCP	Veritas
Citrix	Exin	Huawei	Legato	Nortel	See-Beyond	Vmware
CIW	ExtremeNetworks	Hyperion	Lotus	Novell	Google	

You have made the
Right Choice

You are becoming member of most comprehensive, accurate, highest quality and lowest cost certification resource in the world.

