

HP

Implementing HP Enterprise Virtual Array Solutions

Visit: http://www.pass4sureofficial.com/exams.asp?examcode=HP0-678

Pass4sureofficial.com is a reputable IT certification examination guide, study guides and audio exam provider, we not only ensure that you pass your HP0-678 exam in first attempt, but also you can get a high score to acquire HP certification.

If you use pass4sureofficial HP0-678 Certification questions and answers, you will experience actual HP0-678 exam questions/answers. We know exactly what is needed and have all the exam preparation material required to pass the exam. Our HP exam prep covers over 95% of the questions and answers that may be appeared in your HP0-678 exam. Every point from pass4sure HP0-678 PDF, HP0-678 review will help you take HP HP0-678 exam much easier and become HP certified. All the Questions/Answers are taken from real exams.

Here's what you can expect from the Pass4sureOfficial HP HP0-678 course:

- * Up-to-Date HP HP0-678 questions taken from the real exam.
- * 100% correct HP HP0-678 answers you simply can't find in other HP0-678 courses.
- * All of our tests are easy to download. Your file will be saved as a HP0-678 PDF.
- * HP HP0-678 brain dump free content featuring the real HP0-678 test questions.

HP HP0-678 certification exam is of core importance both in your Professional life and HP certification path. With HP certification you can get a good job easily in the market and get on your path for success. Professionals who passed HP HP0-678 exam training are an absolute favorite in the industry. You will pass HP HP0-678 certification test and career opportunities will be open for you.



QUESTION 1:

How much rack unit space does an HSV2xx controller pair use?

A. 1.5U

B. 2U

C. 3U

D. 4U

Answer: D

QUESTION 2:

The command View EVAPerf enables you to monitor and display what EVA performance metrics? (Select thee.)

- A. Vraid level data
- B. Replication data
- C. Virtual Disk Data
- D. Port Status Data
- E. Quorum disk data
- F. Controller cache data

Answer: B,C,D

QUESTION 3:

How can the status of a specific EVA controller cache battery be checked?

- A. From the controller's EAB port
- B. by running controller diagnostics
- C. From Controller properties in command View EVA
- D. By Checking the battery status LED on the back panel of the controller

Answer: C

QUESTION 4:

You have a disk group that contains twelve 72GB and twelve 146GB disks. The occupancy level of each 72GB disk is approximately 36GB. What is the approximate occupancy level of each 146GB disk?

A. 36GB

B. 72GB

C. 108GB

D. 145GB

Answer: B

QUESTION 5:

What does the EMU do? (Select two.)

- A. Monitors disk enclosure temperatures
- B. Monitors light wave strength of eh FC-AL port
- C. Monitors disk enclosure and controller temperature sensors
- D. Reports disk enclosure events through the Enclosure Address Bus (EAB)
- E. Reports logical disk read failure events through the Enclosure Address Bus (EAB)

Answer: A,D

QUESTION 6:

When using Instant Support Enterprise Edition (ISEE), which method is used to transport error information to HP?

- A. Internet
- B. SNMP traps
- C. Exchange Mail
- D. Secure dial up line
- E. Call-back modem

Answer: A

QUESTION 7:

What settings can the virtual disk cache policy be set to?

- A. Read cache policy set on or off, default is on
- B. Adjust the read/write percentage cache levels
- C. Mirrored or unmirrored write-back cache; default is unmirrored
- D. Mirrored or unmirrored write-through cache; default is mirrored

Answer: A

QUESTION 8:

Which array and services are included with the EVA6000 product?

A. 3-year hardware support, with 4-hour response on a 24x7 basis and 1-year, 24x7 XCS phone-in support and updates

- B. Array installation and startup service, 2-year hardware support with 4-hour response on a 24x7 basis and 2-year, 24x7 XCS phone-in support and updates
- C. Array installation and startup service, 2-year hardware support, with 4-hour response on a 24x7 basis and 3-year, 34x7 XCS phone-in support and updates
- D. Array installation and startup service, 3-year hardware support, with 4-hour response on a 24x7 basis and 1-year, 24x7 XCS phone-in support and updates

Answer: B

OUESTION 9:

On the HSV controller, the OCP cache battery assembly status LED is ON. What does it indicate?

- A. A cache battery is not in use
- B. A cache battery assembly has failed
- C. A Cache battery assembly is operational
- D. The charge level of a cache battery is greater than 50%

Answer: B

QUESTION 10:

What is the best practice when adding disks to a disk group with 12 disks in an EVA 2C6D?

- A. Add disks in multiples of six; distributed evenly across the shelves
- B. Add disks in multiple of ten; distributed evenly across the shelves
- C. Add disks in multiple of eight; distributed evenly across the shelves
- D. Add disks in multiple of fourteen; distributed evenly across the shelves

Answer: C

QUESTION 11:

Why would you configured multiple disk groups instead of a single disk group?

- A. To use different Vraid levels
- B. To achieve higher data availability
- C. To lower the total cost of ownership
- D. To support larger disk volumes spanned across disk groups

Answer: B

QUESTION 12:

You connect a 0C6D expansion rack to a fully equipped 2C1D rack. What is the maximum number of disk drives that can be added to achieve a supported configuration?

A. 56

B. 60

C. 72

D. 8

Answer: C

QUESTION 13:

How can the status of a specific EVA controller cache battery be checked?

- A. From the controller's EAB port
- B. By running controller diagnostics
- C. From controller properties is command View EVA
- D. By checking the battery status LED on the backup panel of the controller

Answer: C

QUESTION 14:

When I/O requests are issued to a Vdisk on the non-owing controller? (Choose two.)

- A. I/O request issued have no performance impact
- B. A read request issued has no performance impact
- C. A write request issued has no performance impact
- D. A read request issued has higher performance impact
- E. A write request issued has a higher performance impact

Answer: C,D

QUESTION 15:

Using command View EVA, which attributes are displayed for HSV2x0 Controller Properties? (Choose three.)

- A. Mirror port states
- B. Temperature sensors
- C. Cache battery module states
- D. Environmental Monitor Unit (EMU)
- E. Levels of protection from shelf failures

Answer: A,B,C

Pass4SureOfficial.com Lifetime Membership Features;

- Pass4SureOfficial Lifetime Membership Package includes over 2500 Exams.
- All exams Questions and Answers are included in package.
- All Audio Guides are included free in package.
- All Study Guides are included free in package.
- Lifetime login access.
- Unlimited download, no account expiry, no hidden charges, just one time \$99 payment.
- Free updates for Lifetime.
- Free Download Access to All new exams added in future.
- Accurate answers with explanations (If applicable).
- Verified answers researched by industry experts.
- Study Material **updated** on regular basis.
- Questions, Answers and Study Guides are downloadable in PDF format.
- Audio Exams are downloadable in MP3 format.
- **No authorization** code required to open exam.
- **Portable** anywhere.
- 100% success Guarantee.
- **Fast**, helpful support 24x7.

View list of All exams (Q&A) downloads http://www.pass4sureofficial.com/allexams.asp

View list of All Study Guides (SG) downloads http://www.pass4sureofficial.com/study-guides.asp

View list of All Audio Exams (AE) downloads http://www.pass4sureofficial.com/audio-exams.asp

Download All Exams Samples http://www.pass4sureofficial.com/samples.asp

To purchase \$99 Lifetime Full Access Membership click here http://www.pass4sureofficial.com/purchase.asp

3COM	CompTIA	Filemaker	IBM	LPI	OMG	Sun
ADOBE	ComputerAssociates	Fortinet	IISFA	McAfee	Oracle	Sybase
APC	CWNP	Foundry	Intel	McData	PMI	Symantec
Apple	DELL	Fujitsu	ISACA	Microsoft	Polycom	TeraData
BEA	ECCouncil	GuidanceSoftware	ISC2	Mile2	RedHat	TIA
BICSI	EMC	HDI	ISEB	NetworkAppliance	Sair	Tibco
CheckPoint	Enterasys	Hitachi	ISM	Network-General	SASInstitute	TruSecure
Cisco	ExamExpress	HP	Juniper	Nokia	SCP	Veritas
Citrix	Exin	Huawei	Legato	Nortel	See-Beyond	Vmware
CIW	ExtremeNetworks	Hyperion	Lotus	Novell	SNIA	

